

No.	Description of Article and Rate.					Per	Tenderer.
	Ridging, galvanized-iron, 22 gauge, with 2 in. lead edges in addition—						
228	16 in.	/6	ft.
229	18 in.	/6½	„
230	20 in.	/7¾	„
231	24 in.	/8½	„
	Ridging, galvanized-iron, 24 gauge, with 2 in. lead edges in addition—						
232	16 in.	/5½	„
233	18 in.	/5¾	„
234	20 in.	/6½	„
235	24 in.	/7½	„
	Spouting, ridging and downpipe, at per cent. discount from New Zealand galvanized-spouting list—						
236	22 gauge	35	per cent.
237	24 gauge	51	„
238	Fittings, 22 gauge	30	„
239	Fittings, 24 gauge	46	„
	Stove-piping, black—						
244	5 in., 16 gauge	/7	ft.
245	6 in., 16 gauge	/8	„
	Stove-piping, galvanized—						
246	5 in., 20 gauge	/9	„
247	6 in., 20 gauge	/10½	„
	Stove-piping, elbows, black, 1 ft. each way from point—						
248	5 in., 16 gauge	2/	each
249	6 in., 16 gauge	2/6	„
	Stove-piping, elbows, galvanized, 1 ft. each way from point—						
250	5 in., 20 gauge	1/9	„
251	6 in., 20 gauge	2/	„
	Tanks, iron, galvanized, corrugated, round, 24-gauge sides, 22-gauge bottom, with cover, waste-pipe 1 in., brass tap, and wash-out plug at bottom—						
254	400 gallons	42/	„
255	600 gallons	60/	„
256	800 gallons	74/6	„
	Tents, strong, double-seamed, with ropes, grommets, and beackets complete—						
	Calico—						
257	8 ft. x 10 ft.	19/3	„
258	10 ft. x 12 ft.	26/3	„
	White duck, 8 oz.—						
259	8 ft. x 10 ft.	25/3	„
260	10 ft. x 12 ft.	34/3	„
	Tent-flies, strong, double-seamed and roped inside hem—						
	Calico—						
261	10 ft. x 12 ft.	9/6	„
262	12 ft. x 14 ft.	13/6	„
263	14 ft. x 16 ft.	18/	„
	White duck, 8 oz.—						
264	10 ft. x 12 ft.	14/	„
265	12 ft. x 14 ft.	20/6	„
266	14 ft. x 16 ft.	26/9	„