

No.	Description of Article and Rate.	Per	Tenderer.
Hose, delivery, indiarubber, armoured, for hot water and steam, to resist 250 lb. pressure, Perdriau Rubber Company's "Red" quality—			
888	½ in. x 5-ply /11	ft.	25 Perdriau Rubber Co. (Ltd.).
889	1½ in. x 6-ply 2/6	,,	
Hose, suction, indiarubber, wire-embedded, smooth bore, 30 ft. lengths, Dunlop Rubber Company of Australia, "Dunlop" quality—			
890	1½ in. x 3-ply 1/5	,,	60 Dunlop Rubber Co. (Ltd.).
891	1¾ in. x 3-ply 1/8	,,	
892	2 in. x 5-ply 2/3	,,	
893	2½ in. x 5-ply 2/5	,,	
894	2½ in. x 5-ply 2/7	,,	
900	Indiarubber, sheet, white, Vulcanized, Perdriau Rubber Company's "Special" quality	2/	75 Perdriau Rubber Co. (Ltd.).
906	Indiarubber insertion, sheet, white, vulcanized, Perdriau Rubber Company's cloth insertion, No. 3 quality	1/1	
Iron, bar, angle, trade lengths—			
907	Equal, Netherton Crown, best or equal quality ..	250/	191 Stewart Timber Co. (Ltd.).
909	Equal, R.H. Crown, or equal quality	235/	
910	Unequal, R.H. Crown, or equal quality	250/	193 Briscoe and Co. (Ltd.).
<i>Extra prices per ton</i> to be added to the tender-rates for angle iron, items Nos. 907, 909, and 910, for the following sizes:—			
Small sizes—			
½ in. thick .. x ½ in. ⅝ in. ¾ in. 1 in. 1¼ in. 1½ in. & up.			
⅝ in. thick .. x			
¾ in. thick .. x			
1 in. thick .. x			
Large sizes (ordinary thickness)—			
4½ in., 5 in., 5½ in., 6 in.			
As per tenders.			
Iron, bar, flat, trade lengths—			
911*	Netherton Crown, best or equal quality, W. Cooke and Co.'s	240/	191 Stewart Timber Co. (Ltd.).
912*	R.H. Crown or equal quality	212/6	193 Briscoe and Co. (Ltd.).
<i>Extra prices per ton</i> to be added to the tender-rates for flat iron, items Nos. 911 and 912, for the following sizes:—			
¾ in. broad .. x ¾ in. 1 in. 1¼ in. 1½ in. 1¾ in.			
1 in. broad .. x			
1¼ in. broad .. x			
1½ in. broad .. x			
1¾ in. broad .. x			
2 in. broad .. x			
2¼ in. broad .. x			
2½ in. broad .. x			
1 in. broad and upwards .. x			
As per tenders.			
Extra widths, ordinary thickness, over 6 in. to 7 in.,			
Extra widths, ordinary thickness, over 7 in. to 8 in.,			
Extra widths, ordinary thickness, over 8 in. to 12 in.,			
Heavy flats, 6 in. and over x 1½ in. and over,			
Heavy flats, 4 in. to 5 in. x 2 in. to 2½ in. and over,			

*See Conditions of Contract for specification.