

No.	Description of Article and Rate.	Per	Tenderer.	
138	Cocks, ball, H.P., full way— ½ in.	2/8	185 A. and T. Burt (Ltd.).	
139	¾ in. } Including copper ball (extra strong) and lever	3/9		
140	1 in. } complete	5/6		
141	2 in. }	24/9		
	Drain-pipes, stoneware, double-glazed, socketed*—			
142	3 in.	5½	188 Thos. Ballinger and Co. (Ltd.).	
143	4 in.	5¾		
144	6 in.	8		
145	9 in.	1/3		
146	12 in.	1/9		
147	15 in.	2/9		
148	18 in.	3/6		
	Drain-pipes, stoneware, double-glazed, straight (without socket)—			190 Herbert Hill and Co.
149	3 in.	4		
150	4 in.	4½		
151	6 in.	7		
152	9 in.	1/		
	Drain-tiles, red, field—			
153	4 in.	21/	100 ft.	
154	6 in.	36/		
155	9 in.	75/		
156	Fire-bricks, standard size	200/	1,000	195 Peter Hutson and Co. (Ltd.).
157	Fire-clay	3/6	cwt.	19 J. J. Craig (Ltd.).
158	Flannel, scouring, to sample (English)	7½	yard	202 Sargood, Son, and Ewen (Ltd.).
164	Glue, best quality—			
	Joiners'	6	lb.	199 Smith and Smith (Ltd.).
	Cabinet	7	"	
	Hose-pipe, best chrome-tanned leather, copper-riveted, to be provided with 1½ in. by 9 in. gusset-piece let in at end—			
168	4 in. diameter	5/9	ft.	194 Briscoe and Co. (Ltd.).
169	6 in.	7/9	"	
170	7 in.	8/9	"	
171	8 in.	10/	"	
172	9 in.	11/9	"	
173	12 in.	17/	"	
	Leather—			
189	Basil-skins, best saddlers' (20 lb. per doz., minimum) unstrained	42/	doz.	
190	Belt, approved quality, in backs	3/	lb.	194 Briscoe and Co. (Ltd.).
191	Bridle, in sides	36/	side	
192	Cow, alum-tanned, white hide, shaved	62/	full hide	
193	Cow, alum-tanned, white hide, shaved	31/6	side	
194	Cow, bag-hide, brown	62/	full hide	
195	Cow, bag-hide, brown	31/6	side	
196	Harness, black (sides not under 20 lb.)	2/1	lb.	
197	Hydraulic, oil-tanned	1/10½	"	
198	Kip, brown or black (not under 9 lb. per side)	2/4½	"	
199	Pipe, hide	2/	"	
200	Pump butts	3/	"	
201	Sole, approved quality (in sides not under 22 lb.)	1/9½	"	
203	Laces, belt, chrome-tanned, equal to sample	3/10	"	

* NOTE.—Double junctions, square or V, to be charged as three pipes; single junctions, square or V, elbows, and heads, as two pipes.