NEW ZEALAND GALVANIZED-IRON SPOUTING LIST.

O.G. spouting					4 in.	$4\frac{1}{2}$ in.	5 in.	6 in,
					4d.	$4\frac{1}{2}$ d.	5d.	6d.
Half-round spouting		3 iı	a.	3 1 in.	4 in.	$4\frac{1}{2}$ in.	5 in.	6 in.
		$2\frac{3}{4}$		3¼d.	3 <u>3</u> d.	4 ₄ d.	4 ¾d .	$5\frac{3}{4}$ d.
Downpipe				1 1 in	2 in.	$2\frac{1}{2}$ in.	3 in.	4 in.
				3½d.	$3\frac{1}{2}d$.	4 1 d.	5d.	6 <u>1</u> d.
Ridging				12 in.	14 in.	16 in.	18 in.	20 in.
(Lead edging ex	tra.)	• •	••	5d.	5¾d.	6½d.	7¼d.	8d.
Heads		40 /- per	doz.	O.G. bracket	ts	••	7 /- per	doz.
Shoes		22/-	- 1	Half-round 1		• •	0.70	,,
Angles		30 /-	,, r	Гubes	• •	• •	6 /- per	gross.
Ridging-clips		6/-	,,	Spikes	• •	• •	447	,, ·

1st September, 1905.

This cancels all previous lists.

By Authority: JOHN MACKAY, Government Printer, Wellington.