

No.	Description of Article and Rate.	Per	Tenderer.
Brushes— <i>continued.</i>			
Sash-tools, forked, string-bound, best-quality bristles—			
48	No. 1	3/2 doz.	42 Bunting & Co. (Ltd.).
49	No. 2	3/9 "	"
50	No. 3	4/11 "	"
51	No. 4	6/3 "	"
52	No. 5	8/7 "	"
53	No. 6	11/4 "	"
54	No. 7	14/10 "	"
55	No. 8	18/7 "	"
56	No. 9	21/4 "	"
57	No. 10	29/8 "	"
58	No. 11	34/4 "	"
59	No. 12	39/ "	"
Sash-tools, pressed ferrule, best-quality bristles—			
60	No. 4	2/3 "	"
61	No. 6	2/10 "	"
62	No. 8	3/9 "	"
63	No. 10	5/ "	"
64	No. 12	7/ "	"
Stock, 3-knot, unground, C.W.B., best quality, grey middles—			
74	6/0	81/2 "	"
75	7/0	101/5 "	"
Varnish, flat, oval-bevelled, C.W.B., best selected white bristles—			
76	2/0	21/2 "	"
77	3/0	31/3 "	"
78	4/0	45/3 "	"
79	5/0	56/3 "	"
Weatherboard, brass-bound, best-quality grey bristles—			
84	4 in.	50/9 "	"
85	5 in.	78/10 "	"
Whitewash, tin-bound, lacquered ferrule, mixed middles white bristles outside—			
86	5 in.	13/6 "	89 D. McLean.
87	6 in.	15/6 "	82 Forsyth and McKay.
88	7 in.	17/9 "	89 D. McLean.
Buckets—			
Iron, 26 gauge, strapped, seamed, and riveted, galvanized after being made—			
89	13 in.	29/ "	89 D. McLean.
90	14 in.	34/ "	82 Forsyth and McKay.
91	15 in.	49/ "	89 D. McLean.
Iron, contractors', heavy-strapped, seamed, and riveted, double-hooped, 22 gauge, with heavy lugs, galvanized after being made, to sample—			
92	13 in.	48/ "	82 Forsyth and McKay.
93	14 in.	54/ "	89 D. McLean.
95	Cans, water, oak-japanned, 2 gallons.. .. .	4/6 each	"
98	Cement, Portland*.. .. .	3/10 cwt.	10 Wilson's Portland Cement Company (Ltd.).

* Cement must be in accordance with the latest British standard specification.