

| No.  | Description of Article and Rate.   |    |    |    |    |    |      |           | Per                       | Tenderer. |
|------|--|----|----|----|----|----|------|-----------|---------------------------|-----------|
|      | Nails, clout, best wrought, flat head, galvanized—   |    |    |    |    |    |      |           |                           |           |
| 1198 | ½ in. . . . .  | .. | .. | .. | .. | .. | /8   | lb.       | 233 G. H. Gothard (Ltd.). |           |
| 1199 | ¾ in. and ⅝ in. . . . .  | .. | .. | .. | .. | .. | /8   | "         | "                         |           |
| 1200 | 1 in. and 1½ in. . . . .   | .. | .. | .. | .. | .. | /7½  | "         | 57 Bailie and Co. (Ltd.). |           |
| 1201 | 1½ in. to 2 in. . . . .  | .. | .. | .. | .. | .. | /8   | "         | 233 G. H. Gothard (Ltd.). |           |
| 1202 | Nails, clout, countersunk, strong, 2½ in. . . . .  | .. | .. | .. | .. | .. | 30/  | cwt.      | 57 Bailie and Co. (Ltd.). |           |
|      | Nails, finishing—  |    |    |    |    |    |      |           |                           |           |
| 1204 | ½ in. . . . .  | .. | .. | .. | .. | .. | /8   | lb.       | 120 Martin and Co.        |           |
| 1205 | ¾ in. . . . .  | .. | .. | .. | .. | .. | /7   | "         | "                         |           |
| 1206 | ⅔ in. . . . .  | .. | .. | .. | .. | .. | /6   | "         | "                         |           |
| 1207 | ⅝ in. . . . .  | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
| 1208 | 1 in. . . . .  | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
| 1209 | 1½ in. . . . .   | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
| 1210 | 1½ in. . . . .   | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
| 1211 | 1¾ in. . . . .   | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
| 1212 | 2 in. . . . .  | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
| 1213 | 2½ in. . . . .   | .. | .. | .. | .. | .. | /5½  | "         | "                         |           |
|      | Nails, wire, diamond head, or rose head, as required—  |    |    |    |    |    |      |           |                           |           |
| 1215 | 1 in. x 15 gauge . . . . .   | .. | .. | .. | .. | .. | 21/  | cwt.      | 233 G. H. Gothard (Ltd.). |           |
| 1216 | 1¼ in. x 14 gauge . . . . .  | .. | .. | .. | .. | .. | 20/  | "         | "                         |           |
| 1217 | 1½ in. x 13 gauge . . . . .  | .. | .. | .. | .. | .. | 19/  | "         | "                         |           |
| 1218 | 2 in. x 12 gauge . . . . .   | .. | .. | .. | .. | .. | 17/6 | "         | "                         |           |
| 1219 | 2½ in. x 11 gauge . . . . .  | .. | .. | .. | .. | .. | 17/  | "         | "                         |           |
| 1220 | 2½ in. x 10 gauge . . . . .  | .. | .. | .. | .. | .. | 16/3 | "         | 57 Bailie and Co. (Ltd.). |           |
| 1221 | 3 in. x 9 gauge . . . . .  | .. | .. | .. | .. | .. | 15/6 | "         | 233 G. H. Gothard (Ltd.). |           |
| 1222 | 3½ in. x 6 and 7 gauge . . . . .   | .. | .. | .. | .. | .. | 14/3 | "         | 57 Bailie and Co. (Ltd.). |           |
| 1223 | 4 in. x 6 gauge . . . . .  | .. | .. | .. | .. | .. | 13/9 | "         | 233 G. H. Gothard (Ltd.). |           |
| 1224 | 5 in. x 5 gauge . . . . .  | .. | .. | .. | .. | .. | 13/9 | "         | "                         |           |
| 1225 | 6 in. x 4 gauge . . . . .  | .. | .. | .. | .. | .. | 13/9 | "         | "                         |           |
| 1226 | Nails, wire, Evenden's spring-head, galvanized . . . . .   | .. | .. | .. | .. | .. | 1/3  | gross     | "                         |           |
| 1228 | Netting, wire, galvanized after manufacture, any width or mesh, at per cent. discount off list No. 4 . . . . . | .. | .. | .. | .. | .. | 45   | per cent. | "                         |           |

## NUTS (Whitworth's Standard Threads and Sizes).

*Iron, Black, Machine-made.*

Bayliss, Jones, and Bayliss (Limited), Wolverhampton.

| Size. | Per Gross.   |       |       |       | Per Cwt. |       |             |       |        |        |                                |        |       |
|-------|--|-------|-------|-------|----------|-------|-------------|-------|--------|--------|--------------------------------|--------|-------|
|       | ½ in.  | ¾ in. | ⅔ in. | ⅜ in. | ½ in.    | ¾ in. | ⅔ to 1⅓ in. | ⅔ in. | 1⅓ in. | 1⅔ in. | 1⅔ in.                         | 1⅔ in. | 2 in. |
| 1230  | Square, tapped   | 2/    | 2/    | 2/3   | 2/6      | 31/   | 26/6        | 25/6  | 25/6   | 28/6   | —                              | —      | —     |
| 1232  | Hexagon, tapped  | 2/3   | 2/3   | 2/6   | 2/9      | 36/   | 32/         | 30/   | 30/    | 31/6   | —                              | —      | —     |
| 1264  | Oakum . . . . .  | ..    | ..    | ..    | ..       | ..    | ..          | 36/   |        | cwt.   | 233 G. H. Gothard (Ltd.).      |        |       |
| 1265  | Oil, gas-engine, cylinder, Tangye's . . . . .                    | ..    | ..    | ..    | ..       | ..    | ..          | 4/    |        | gal.   | 120 Martin and Co.             |        |       |
| 1267  | Oil, kerosene, 150° Fahr., in Abel's closed tester, "White Rose" |       |       |       |          |       |             | /11½  |        | "      | 224 Vacuum Oil Company (Ltd.). |        |       |
|       | Oil-feeders, common—   |       |       |       |          |       |             |       |        |        |                                |        |       |
| 1272  | 1 pint . . . . .   | ..    | ..    | ..    | ..       | ..    | ..          | 22/   |        | doz.   | 57 Bailie and Co. (Ltd.).      |        |       |
| 1273  | 2 pints . . . . .  | ..    | ..    | ..    | ..       | ..    | ..          | 24/   |        | "      | "                              |        |       |