

No.	Description of Article and Rate.						Per	Tenderer.
	Brushes— <i>continued.</i>							
	Sash-tools, pressed ferrule, best-quality bristles—							
60	No. 4	2/3	doz.	42	Bunting and Co. (Ltd.).			
61	No. 6	2/10	"		"			
62	No. 8	3/9	"		"			
63	No. 10	5/	"		"			
64	No. 12	7/	"		"			
	Stock, 3-knot, unground, C.W.B., best quality, grey middles—							
74	6/0	81/2	"		"			
75	7/0	101/5	"		"			
	Varnish, flat, oval-bevelled, C.W.B., best selected white bristles—							
76	2/0	21/2	"		"			
77	3/0	31/3	"		"			
78	4/0	45/3	"		"			
79	5/0	56/3	"		"			
	Weatherboard, brass-bound, best quality grey bristles—							
84	4 in.	50/9	"		"			
85	5 in.	78/10	"		"			
	Whitewash, tin-bound, lacquered, ferrule, mixed middles, white bristles outside—							
86	5 in.	23/3	"		"			
87	6 in.	29/3	"		"			
88	7 in.	38/	"		"			
	Buckets—							
	Iron, 26 gauge, strapped, seamed, and riveted, gal- vanized after being made—							
89	13 in.	17/	"	56	Bailie and Co. (Ltd.).			
90	14 in.	18/9	"		"			
91	15 in.	20/3	"		"			
	Iron, contractors', heavy-strapped, seamed, and riveted, double-hooped, 22 gauge, with heavy lugs, galvanized, after being made, to sample—							
92	13 in.	38/	"		"			
93	14 in.	42/	"		"			
94	15 in.	46/	"		"			
97	Cans, watering, galvanized, with rose, 10 quarts ..	5/6	each		"			
98	Cement, Portland*	3/10	cwt.	9	Wilson's Portland Cement Company (Ltd.).			
	Closet-pans, galvanized—							
99	Large size, to sample	10/6	each	231	G. H. Gothard (Ltd.).			
100	Small size, to sample	9/6	"		"			
	Cocks, brass, H.P. bib, screwed, New Zealand pattern—							
	With hose union—							
103	½ in.	2/6	"		"			
104	¾ in.	3/8	"		"			
105	1 in.	5/	"		"			
106	1¼ in.	11/6	"		"			
	Without hose union—							
109	½ in.	2/	"		"			
110	¾ in.	3/	"		"			
111	1 in.	4/6	"		"			
112	1¼ in.	10/	"		"			
113	1½ in.	15/6	"		"			

* Cement must be in accordance with the latest British standard specification.