[No. 31

0.G. spouting	•• •	••	••	••	••	4 in. <b>4d.</b>	4½ in. 4½d.	5 in. <b>5d.</b>	6 in. <b>6d.</b>
Half-round spoutin	g ••	•••	••	3 in. <b>2¾d.</b>	3½ in. <b>3¼d.</b>	4 in. <b>3¾d.</b>	4½ in. <b>4¼d.</b>	5 in. <b>4¾d.</b>	6 in. <b>5<u>3</u>d</b> .
Downpipe	•••	••	••		1½ in. 3½d.	2 in. <b>3½d.</b>	2 <del>1</del> in. <b>411 d.</b>	3 in. <b>5d</b> .	4 in. <b>6<u>4</u>d.</b>
Ridging (Lead edgi		••	••,	••	12 in. <b>5d.</b>	14 in. <b>5¾d.</b>	16 in. <b>6½d.</b>	18 in. <b>74d.</b>	20 in. <b>8d.</b>
Heads Shoes Angles		•••	22/- 30/-	; ,,	Tubes .	kets l brackets 	 	7/- per doz. 3/6 " 6/- per gross.	
Ridging-clips .	••••	• • •	6/-	"	Spikes .			12/-	,,

## NEW ZEALAND GALVANIZED-IRON SPOUTING LIST.

1st September, 1905.

This cancels all previous lists

By Authority: JOHN MACKAY, Government Printer, Wellington.