## SCHEDULE 11.—METALS AND METAL MANUFACTURES.

Item No		Des <b>crip</b> tion	•			Rate.	At per	Contractor.
1014	Baths, plunge, taper, ro	ll edge. g	alvanized	iron, on	cast-			
	iron feet (complete Boilers, copper, all size	with plug				60/	each	A. and T. Burt (Lto Christchurch.
1015	Brazed					3/	lb.	Ditto.
1016	Solid-drawn					3/6	,,	Ashby, Bergh, and
	Buckets, galvanized iros strapped bottoms	n, hoope	d, seamed	, and ri	veted,	,	,,	(Ltd.), Christchurch.
1023	12 in. diameter		•••		• •	<b>35</b> /	doz.	Ditto
1024	13 in. diameter					<b>3</b> 7/	. ,,	; ;;
1025	14 in. diameter		••			41/	,,	· • • • • • • • • • • • • • • • • • • •
	Buckets, contractor's, ga double-hooped, se ears—							
1026	13 in		• •	• •	• •	<b>78</b> /	,,	,,
1027	14 in		• •	• •		81/	,,	,,
	Copper—							
1029	Plates, trade sizes, 1	in. to 1	in	••		3/	lb.	***
	Rods, trade lengths-	_						4
1030	$\frac{1}{4}$ in. to $\frac{7}{16}$ in.					3/	,,	22
1031	½ in. up	••				3/	,,	,,,
	Sheets, trade sizes—					•		,,
1032	26 gauge					3/3	,,	,,
1033	24 gauge	••				3/	,,	,,
1034	22 gauge and heav					3/	,,	,,
1035	Lead, ingot					<b>42</b> /	cwt.	,,
1000	Lead, sheet, 3 lb. to 8 l		•••	••		/	0 50	-
1036	Full rolls		1			44/		
1037	Cut across roll	••	• • •	••	l	48/	,,	,,
1038		ohoma ar	d offente	(nromin	m on	$32\frac{1}{2}$	per cent.	A. and T. Burt (Ltd
1030	Lead, bends, traps, siphons, and offsets (premium on New Zealand trade list, March, 1915) Muntz-metal rods—					922	per cent.	Christchurch.
1039						3/	lb.	Ashby, Bergh, and
	¼ in. to ¾ in	• •		••	••		10.	(Ltd.), Christchurch.
1040	$\frac{7}{16}$ in. up	• • •	• •	• •	• •	3/	,,	Ditto.
1041	Muntz-metal sheets, an					3/3	,,	,,
1042	Pans, closet, oval, galvanized, with side handles, 22 gauge, 4-gallon Pipe, down, galvanized, 6 ft. or 8 ft. lengths (premium				9/6	each	A. and T. Burt (Ltd. Christchurch.	
	on current New Zealand trade list)—							
1043	22 gauge		:		••	$33\frac{1}{3}$	per cent.	Ashby, Bergh, and (Ltd.), Christchurch.
1044	24 gauge					40	,,	Ditto.
	Ridging, galvanized, p			-				, e
1054	24 gauge	• •				40	,,	,,,
1055	26 gauge					<b>2</b> 0	, , ,	,,,
	Ridging, galvanized, with 26 gauge—		dges, 2 in	. (4 lb. s	trips),			
1059	16 in. (inclusive of	lead)				1/4	ft.	. ,,
1059a	18 in. (inclusive of	lead)				1/ <b>5</b>	,,	<b>,,</b>
1060	20 in. (inclusive of	lead)		• •		1/6	,,	,,
1061	22 in. (inclusive of	lead)	• •			1/7	,,	<b>,,</b>
	Spouting, galvanized, C		alf-round	, 6 ft. oı	8 ft.			
	lengths (premium							
	24 gauge		• •			<b>3</b> 0	per cent.	,,
1064								