ACCEPTED TENDER-RATES FOR STORES REQUIRED BY THE NEW ZEALAND GOVERNMENT DURING THE YEAR ENDING 80th JUNE, 1920.

To be supplied in accordance with the Terms and Conditions of Contract signed by the Chairman, Public Service Stores Tender Board, and dated 26th March, 1919.

AT TAURANGA.

SCHEDULE 1.—BRICKS, DRAINPIPES, ETC.

Item No.		Decori	ption.			Rate, 1st Class.	Rate, 2nd Class.	At per	Contractor.
	Drainpipes, sto			azed, soc	keted,				
	in 2.ft. l	$_{ m lengths}$	•						
1	3 in.	• •	••	• •	••	$1/7\frac{1}{2}$	$1/6\frac{1}{2}$	Each	The Earthenware Pipe Co. (Ltd.), Auckland.
2	4 n.	•,•			• •.	$1/9\frac{1}{2}$	$1/8\frac{1}{2}$,,	Ditto.
3	6 in.					$2/6\frac{1}{2}$	$2/5\frac{1}{2}$,,,	29
4	9 in.	• •	• •	• •		$4/6\frac{1}{2}$	$4/4\frac{1}{2}$,,	,,
5	12 in.	• •				6/5	$6/3\frac{1}{2}$,,	,,
6	15 in.		• •			9/10	9/3	,,	,,
7	18 in.		• •			12/11	12/4	,,·	,,
8	21 in.		• •			19/1	18/3	,,	,,
9	24 in.					24/2	21/	,,	,,
	Fittings for-	_							
	Bends, to	be price=	of 2 pip	es, as pe	r trade	custom.			
	Juncti	ons, squ	are or Y	(s ze of	main p	oipe irre-	D. (
	spectiv	ve of size	e of bran	ch)—			Rate, 1st Class.		-
。 10	3 in.						3/5	,,	,,
11	4 in.				٠		3/10	,,	,,,
12	6 in.						5/1	,,	,,
13	9 in.						8/6	,,	,,,
14	12 in.						12/4	,,	,,,
15	15 in.						18/2	,,	,,
16	18 in.	• •					24/4	,,	,,
17	21 in.						35/9	,,	,,
18	24 in.			••			46/	",	,,
	Field drainpipe						'	,,	"
19	2 in.	••-	••		••	••	13/6	100	J. J. Craig (Ltd.), Auck land.
20	3 in.						19/		Ditto.
21	4 in.	• • • • • • • • • • • • • • • • • • • •	••			• • • • • • • • • • • • • • • • • • • •	24/	,,	
22	6 in.		• • •	••		• • •	47/6	,,	"
22	Inspection-pipe	••	••	••	••	••	1.,0	,,	*,
23	4 in.	• •			••	••	$6/2\frac{1}{2}$	each	The Earthenware Pipe Co (Ltd.), Auckland.
24	6 in.						$9/8\frac{1}{2}$		Ditto.
21	Siphons—	••	••	••	••	••	0,02	,,	2100.
25	4 in.						9/		
26	6 in.	••	••	••	• •		12/9	,,	,,
27	9 in.	••	••	••	•••	••	19/4	,,	"
41	Gully-traps, ordinary—					••	10/1	"	,,
90	3 in.	umary-					8/1		
28		• •	••	••	••	• •		,,	,,
29	4 in.	• •	••	• • •	• •	••	8/1	,,	,,
30	6 in.	 	 4h4 :	··	· ·	• •	10/8	,,	,,
0.1	Gully-traps, H						90 /9		
31	4 in. outlet					1 1	20/3	,,	,,
32	4 in. inlets	and 4 in	. outlets 2	k 12 in. d	1sh x 2	n. seal	22/5	,,	"