

| Tariff Item No. | Goods | Rates of Duty | | | | | Con- cessional Reference | Concession Effective Until* |
|-------------------------------------|---|---------------|------|------|------|------|--------------------------------|-----------------------------------|
| | | B.P. | Aul. | Can. | MFN. | Gen. | | |
| 719.930.9 | Cables, flexible, and sleeves, for attaching to hand pieces of dental engines | Free | .. | .. | 20%S | 25% | 10-2 | 31/12/65 |
| 719.990.1 | Lubricators, on declaration by a manufacturer that they will be used by him solely in the completion of articles in New Zealand | Free | .. | .. | .. | Free | 10-8 | 30/6/64 |
| 723.101.1 723.102.1 723.103.1 | Wires and cables as may be approved, etc.: .. | Free | .. | .. | 20%S | 25% | .. | 30/6/65 |
| | Approved: | | | | | | | |
| | Armoured cables | | | | | | | |
| | Cables, all kinds, having eight or more cores | | | | | | | |
| | Cables and wires insulated with polytetrafluoroethylene (P.T.F.E.) | | | | | | | |
| | Cables and wires insulated solely with paper, cotton, silk, wool, rayon, nylon, glass, enamel, cambric, or any combination of these materials with asbestos, and whether or not varnished | | | | | | | |
| | Cables and wires sheathed in lead, copper or aluminium | | | | | | | |
| | Cables and wires specially suited for use in aircraft wiring, on declaration that they will be used only for that purpose | | | | | | | |
| | Carrier quad cables, metal tape screened, also four quad and above, unscreened | | | | | | | |
| | Coaxial cables | | | | | | | |
| | High tension X-ray cable | | | | | | | |
| | Jumper cables | | | | | | | |
| | Messenger wire cable, being electrical conductors bound to a supporting or bearing wire | | | | | | | |
| | Radio wire, P.V.C. insulated, single core, 7/·004 in. and 7/·0048 in. | | | | | | | |
| | Service entrance cables, neutral screened, single or multi-core | | | | | | | |
| | Silicone rubber covered cables, wires and flexibles | | | | | | | |
| | Telephone hand set and switchboard cords | | | | | | | |
| | Telephone subscribers' cables, metal tape screened, also eight pairs and above unscreened | | | | | | | |
| | Tough plastic sheathed (TPS) cables, 4 core circular, 7/·036 in. and above | | | | | | | |
| | Tough plastic sheathed (TPS) cables, 4 core flat, with or without earth continuity conductor, in sizes exceeding 7/·044 in. | | | | | | | |
| | Tough plastic sheathed (TPS) cables, 2 core, with or without earth continuity conductors, in sizes exceeding 19/·044 in. | | | | | | | |
| | Tough plastic sheathed (TPS) cables, 3 core, with or without earth continuity conductors, in sizes exceeding 7/·064 in. | | | | | | | |
| | Tough plastic sheathed (TPS) cables, 4 core, in sizes exceeding 7/·064 in. | | | | | | | |
| | Tough plastic sheathed (TPS) cables, all sizes having more than 4 conductors | | | | | | | |
| | Tough rubber sheathed (TRS) cables, 4 core circular, 7/·044 in. and above | | | | | | | |
| | Tough rubber sheathed (TRS) cable, flexible, 5 core, comprising 3 cores 162/·0076, 1 core 110/·0076, and 1 core 23/·0076 | | | | | | | |
| | Tough rubber sheathed (TRS) flexible, exceeding 110/·0076 in. (0·0048 sq. in.), twin, triple, or four core | | | | | | | |
| | Trailing cables conforming to New Zealand Standard Specifications 397 (B.S. 708/1950) or 444 (B.S. 1116/1943), with individual core conductors having a nominal cross-sectional area exceeding 0·0048 sq. in. (110/·0076 in. or equivalent) | | | | | | | |
| | Welding cables having a current rating of 250 amperes or over | | | | | | | |
| | Winding wires | | | | | | | |